







93 S Railroad Avenue Unit C Bergenfield NJ 07621 USA www.enapart.com sales@enapart.com



Via del Canneto 35. Borgosatollo, Brescia - Italia www.enapart.it vendite@enapart.it



Barbaros Mah. Ihlamur Bul. Ağaoğlu My Newwork No:3/15 Ataşehir / İstanbul www.enapart.net satis@enapart.net



PRIVADA 10 B SUR #3908 COL. ANZUREZ, C.P. 72530, PUEBLA, PUE www.enapart.com.mx sales@enapart.com.mx



Friedrich-Ebert-Anlage 36, 60325 Frankfurt am Main, Germany www.enapart.de anfrage@enapart.de



4 boulevard Carnot, 95400 villiers-le-bel, Paris, France www.enapart.fr sales@enapart.fr



65049, ОДЕСА, ВУЛИЦЯ ІВАНА ФРАНКА, БУДИНОК 55, ПОВЕРХ 3 www.enapart.com.ua sales@enapart.com.ua



MUNICIPIUL BUCUREŞTI, SECTOR 3, B-DUL BASARABIA, NR.250, CORP P+5 Hempstead, HP1 3AF , United Kingdom www.enapart.ro sales@enapart.ro



〒584-0023 大阪府富田林市若松町 東2丁目2番16号 www.enapart.co.jp sales@enapart.co.jp



PLAZA NUESTRA SEÑORA DE LAS NIEVES 12 ,LOCAL ,50012,ZARAGOZA www.enapart.es ventas@enapart.es



Складова база "Онгъл", Склад А2, п.к. 4006, гр. Пловдив, България www.enapart.bg sales@enapart.bg



3 Austin Mews, High Street, Hemel www.enapart.co.uk sales@enapart.co.uk





Banner Engineering

Enapart always strives to provide the competitive prices and timings of supplies for its customers. We sell only original equipment and spare parts, although we are not always the official distributor or manufacturer's dealer. All displayed trademarks and part numbers are the property of their respective owners.

BRAND'S PRODUCTS

| Product | Description |
|---------------------------------------|---|
| p/n: 3075424, Type: EA5E300Q | EZ-ARRAY SERIES MEASURING LIGHT CURTAIN |
| 3075425 / EA5E450Q | Measuring light curtain transmitter plug |
| P/N: 3075376 Type: K50APFF100GREQP | sensor |
| 3024983 / K50APTGRCQ | Touch Button |
| K50LGRA1YPQ | Industrial Panel Mount Indicator |
| K50LGRYNQ | Indicator Light |
| LS10-EQDH (10004368 / 25092783) | BANNER PHOTELECTRIC EMITTER |
| <u>LS10RQDH</u> | BANNER 4 PIN EURO QD LIGHT SCREEN RECEIVER |
| OTC-1-YW | BANNER OPTO-TOUCH |
| 3031941 / Q25SP6FF100 | Opto-sensor, reflective light sensor |
| Q45BB6LLPQ6 | rectangle sensor |
| Q45BB6RQ5 | Through-Beam Optical Sensor |
| <u>QS186EQ8</u> | Photoelectric Sensor |
| 3066460 / QS18VP6DQ8 | Sensor |
| QS18VP6LLPQ8 | Retroreflective, Polarized Optical Sensor 32.81' (10m) PNP - Dark-ON/Light-ON |
| QS18VP6LVQ8 | Photoelectric Sensor |
| QS18VP6RQ8 | Photoelectric Sensor |
| P/N: 3002728, Type: QT50ULBQ6 | Ultrasonic sensor reflection sensor |
| 78414 / SA-E12M30 | BANNER MOUNTING BASE ADAPTER/COVER |
| STBVP6Q5 | Photoelectric Sensor |
| TL50GRAQ | |
| 3083214 / TL50GYRAQ | LED Indicator – Tower Light |
| <u>VTBP6Q</u> | Sensor Verification Touch Button |
| LS2TP30-450Q88 | BANNER EZS TYPE2 PAIR PAIR 30MM X 450MM |
| Q45ULIU64ACRQ6 | RADAR SENSOR |
| SMA31EQD | mini-beam series industry standard sensor |
| SM2A312LV | SENSOR, PHOTOELECTRIC, MINI-BEAM RETRO |
| SM30SRL | Opto-sensor |
| <u>3027285</u> | |
| <u>DS3-LD-045</u> | |
| SLSP30-750Q88 | BANNER CAT 4 PAIR |
| K50LGXXPQ | |

Enapart Group





| Product | Description |
|-------------------------|--|
| K50LWXXP | - |
| K50LYXXP | |
| K50LRXALSXP | |
| 3066452 | photosensor |
| SLSR14-450Q8 | BANNER RECEIVER |
| SLSE14-450Q8 | TURCK BANNER EZ-SCREEN EMITTER |
| M12PDQ8 | Photoelectric sensor |
| Q25SN6FF100Q | Sensor |
| M18SP6DLQ | Opto Sensor |
| 3032953 / MQAC-415RA | cordset |
| K50RPFF100GREQ | Bestückungssensor |
| <u>3076046 /</u> | Pick-to-Light Bestückungssensor |
| K50APFF100YREQP | |
| <u>DX70N2X6S4P4M2M2</u> | BANNER SURECROSS |
| DX70G2X6S4P4M2M2 | BANNER SURECROSS |
| DX80N2X6S-PM8 | BANNER WIRELESS |
| QS18VP6LDQ8 (3073045) | Opto Sensor |
| R55CG1QP | Opto Sensor |
| <u>SLPP25-970</u> | Safety light curtain (emitt. + receiv. pair) |
| <u>SLPMP25-970</u> | Ez-Screen Low Profile Muting Pair |
| SLPMR25-1810P12 | |
| SLSCR30-1500P4NT | |
| <u>SC22-3</u> | |
| SLC1BB6 | |
| 10487549 / 54592000 | FIBER OPTIC GLASS |
| WLC90WGL8Q | WLC90 Work Light; Dimensions: 90X90 mm |
| PIAT46UHFMTA | Sensor |
| <u>BT2.53S</u> | HIGH TEMPERATURE FIBER OPTICS |
| QM26VPAF400Q5 | QM26 SERIES WASHDOWN SENSOR |
| BAT26S | ANGLE FIBER OPTICS |
| BAT26P | ANGLE FIBER OPTICS |
| MQDC2S-850 | SINGLE-ENDED CORDSETS |
| <u>IT210SM6</u> | HIGH TEMPERATURE FIBER OPTICS |
| NC50-CP80-VP4X2 | Sensor |
| <u>IF210S</u> | HIGH TEMPERATURE FIBER OPTICS |
| SMA912LV | VALU-BEAM SERIES |
| <u>IAT26SM600</u> | ANGLE FIBER OPTICS |
| VS2KAP5VQ | VS2 SERIES ULTRA THIN MINIATURE SENSOR |
| SM2A912LVQD | VALU-BEAM SERIES |
| SMB915LVAG W/30 | VALU-BEAM SERIES |
| MQDC-1210RA | SINGLE-ENDED CORDSETS |
| T18VP6URQ | T18U SERIES OPPOSED MODE ULTRASONIC SENSOR |
| T18VN6URQ | T18U SERIES OPPOSED MODE ULTRASONIC SENSOR |
| BT28SM8 | HIGH TEMPERATURE FIBER OPTICS |





| Product | Description |
|---------------------|--|
| PIRS1X1630UMPMAL | ARRAY & SLOT FIBER OPTICS |
| <u>IA29S</u> | ANGLE FIBER OPTICS |
| MBCC2-580 | SINGLE-ENDED CORDSETS |
| MAQDC-8100 | SINGLE-ENDED CORDSETS |
| BF1801L-024 | MECHANICAL SWITCHES |
| <u>SLM180B6</u> | SLM SERIES RUGGED METAL SLOT SENSOR |
| QMT42VN6AFV400 | SENSOR |
| QMT42VP6AFV400 | SENSOR |
| BR23P | ARRAY & SLOT FIBER OPTICS |
| IA1.56SMTA | ANGLE FIBER OPTICS |
| PIA46UMAF | ANGLE FIBER OPTICS |
| QS18VP6LLPQ-76914 | QS18 SERIES ALL PURPOSE PHOTOELECTRIC SENSOR |
| MSA-RM-1 | MECHANICAL SWITCHES |
| SBRXF1 | MULTI-BEAM SERIES |
| BAT21.33SMST1 | ANGLE FIBER OPTICS |
| <u>Q85BW13LP</u> | sensors |
| Q85BW13DL | sensors |
| <u>Q85BW13D</u> | sensors |
| RP-LM40D-6L | OPE PULL STOP CONTROL DEVICE |
| QS30RRX W/30 | S30 SERIES HIGH-PERFORMANCE LONG-RANGE SENSOR |
| QS30ARX W/30 | QS30 SERIES HIGH-PERFORMANCE LONG-RANGE SENSOR |
| SMA30PEL | SM30 SERIES 150 M RANGE OPPOSED MODE BARREL SENSOR |
| <u>S18AW3FF50</u> | SENSOR |
| <u>IA28S</u> | ANGLE FIBER OPTICS |
| <u>IT210S</u> | HIGH TEMPERATURE FIBER OPTICS |
| <u>PLI-A10</u> | TIGHT BEND RADIUS FIBER OPTICS |
| MQDC-1210ST | SINGLE-ENDED CORDSETS |
| SM2A912DSRQD | VALU-BEAM SERIES |
| PDIS46UM38MSD66 | ARRAY & SLOT FIBER OPTICS |
| <u>MBCC-460</u> | SINGLE-ENDED CORDSETS |
| <u>IAT27S</u> | Glass Fiber Sensors |
| BA1.54SMETA | Fiber Sensors |
| <u>BF26P</u> | Glass Fiber Sensors |
| K80APPBGXDQ | LIGHT BUTTONS |
| BAT25S | ANGLE FIBER OPTICS |
| <u>IAR23SMA</u> | ARRAY & SLOT FIBER OPTICS |
| <u>BT18S</u> | HIGH TEMPERATURE FIBER OPTICS |
| <u>IAT2.53P</u> | ANGLE FIBER OPTICS |
| <u>IAT2.53SM600</u> | ANGLE FIBER OPTICS |
| Q85VR3LP | Photoelectric Sensor, Polarized Retroreflective, |
| Q85VR3DL | |
| SM312LVQD | BANNER PHOTOELECTRIC SENSOR |
| IA1.53SMTA | |





| Product | Description |
|-----------------|--|
| QH23SP6CV50Q | Sensor |
| OPBT3QDH | |
| MQDC-415RA | wires |
| BWA-QD5.5 | connector |
| BRT-THG-1-100 | BANNER RETROREFLECTIVE TAPE |
| MQD9-415RA | Quick Disconnect Cable |
| QDE-850D | Single-Ended Cordset |
| SMBAMS70AS | Mounting Bracket For Ip68 High Intensity Area, 70M |
| QDE-875D | Single-Ended Cordset |
| T18GRYN | DC-Operated LED Indicators |
| T18GRXN | General Purpose Indicator |
| T18GRXNQ | General-Purpose Indicator |
| T18GXYNQ | General Purpose Indicator |
| S18SN6D W/30 | S18 TYPE SENSOR IN THREADED HOUSING |
| PBP46UM2.5 | Fiber Optic Sensors |
| PIF66UMVFA | fibre-optic cable |
| RPA-C1-10 | ROPE WIRE |
| PIT46UM5 | PLASTIC FIBEROPTIC ASSEMBLY |
| VS25EVQ-69237 | SENSOR |
| EZS-1200 | EZ-SCREEN™ Lens Shields |
| EZA-MBK-13 | SCREEN ACCESSORY RETROFIT |
| EZA-MBK-14 | SCREEN ACCESSORY RETROFIT STI |
| EZA-MBK-15 | SCREEN ACCESSORY RETROFIT KEYANCE SUNX |
| <u>IT23P</u> | Individual Glass Fiber |
| PBPF26UMB | INLINE FIBER OPTICS |
| PBPS66U | ANGLE FIBER OPTICS |
| QS18EP6FPQ8 | FIBER OPTIC AMPLIFIER |
| CL50YXXPQ | LED COLUMN LIGHTS |
| EZSS-1650 | SHIELD EZ SCREEN SNAP-ON |
| Q126E-81524 | Sensor (Photo-electric) |
| MQDC-530RA | SINGLE-ENDED CORDSETS |
| MQDC2S-815RA | SINGLE-ENDED CORDSETS |
| STP-MAQDC-806 | DOUBLE-ENDED CORDSETS |
| <u>VSM4RP6R</u> | Sensor |
| <u>QDC-515C</u> | Sensor Cable |
| <u>EZS-1350</u> | Lens Shields |
| <u>T18GRYNQ</u> | General-Purpose Indicators |
| <u>VS4RN5R</u> | Opposed-Mode Sensors |
| APG30S | Aperture Kit |
| T18RP6LP | Sensor |
| <u>QDU-515C</u> | MICRO-SCREEN Cable |
| SI-QS75MC | PLASTIC COMPACT SAFETY SWITCHES |
| M186E W/30 | METAL BARREL-MOUNT SENSOR |





| Product | Description |
|-------------------|--|
| SI-LS83SD | PLASTIC COMPACT SAFETY SWITCHES |
| SI-LS83SRAD | PLASTIC COMPACT SAFETY SWITCHES |
| SI-LS83SE | PLASTIC COMPACT SAFETY SWITCHES |
| SI-LS83SRAE | PLASTIC COMPACT SAFETY SWITCHES |
| <u>T86EVQ5</u> | SELF-CONTAINED BARREL-MOUNT SENSOR |
| Q12AB6R | MINIATURE SELF-CONTAINED SENSOR |
| Q12AB6RQ | MINIATURE SELF-CONTAINED SENSOR |
| Q12RB6RQ | MINIATURE SELF-CONTAINED SENSOR |
| Q12AP6RQ3 | MINIATURE SELF-CONTAINED SENSOR |
| TL50HGQP | LED TOWER LIGHT |
| K30LMXXPPB2 | GENERAL PURPOSE ILLUMINATED PUSH BUTTONS |
| K30LRXXPPB2Q | GENERAL PURPOSE ILLUMINATED PUSH BUTTONS |
| K30LBXXPPB2Q | GENERAL PURPOSE ILLUMINATED PUSH BUTTONS |
| K30LMXXPPB2Q | COLOR INDICATOR WITH DRY CONTACT SWITCH |
| PBPS46UMT | |
| DS18AP6LPQ8-79909 | WIDE BEAM BARREL-MOUNT SENSOR |
| MQVR3S-530 | SINGLE-ENDED CORDSETS |
| MQDC20-530 | SINGLE-ENDED CORDSETS |
| MQAC-450 | SINGLE-ENDED CORDSETS |
| MQDEC-450SS | DOUBLE-ENDED CORDSETS |
| MQEAC-630 | SINGLE-ENDED CORDSETS |
| TL50ALS | LED TOWER LIGHT |
| Q25SP6R W/30 | RIGHT-ANGLE BASE-MOUNT RECTANGLE SENSOR |
| PIT26UHF | TIGHT BEND RADIUS FIBER OPTICS |
| S18RW3R W/30 | EPOXY ENCAPSULATED BARREL-MOUNT SENSOR |
| PIT46UM14TL | PLASTIC FIBEROPTIC ASSEMBLY & MOD'S |
| Q10RP6RQP2 | Photoelectric Sensor |
| PIL46UHF | FOCUSED & EXTENDED RANGE FIBER OPTICS |
| Q10AP6RQP2 | |
| QS18VP6RQ5-19637 | |
| QS18VP6RQ5 | PHOTOELECTRIC SENSOR |
| <u>FLX30-DM30</u> | Flexible Mounting Arm |
| SMBP4RAS | Right-Angle Swivel Mounting Bracke |
| M18GRBPQ | General Purpose Indicator |
| <u>DELP-1150E</u> | |
| T30RGX8PQ8 | |
| IVURDM-QDK-803 | |
| NI35-CP40-AN6X2 | |
| DBQ5 | Sensor |
| Q10AN6DQ | Photoelectric Sensor |
| Q10RN6D | |
| Q10RN6DQ | Photoelectric Sensor |
| Q10AP6D | Photoelectric Sensor |
| | |





| Product | Description |
|---------------------------------|---|
| IVU LICENSE BCR | Sensor |
| CSB-M1240M1241 | Splitter Cable |
| <u>PIT420U</u> | Fiber Optics |
| DEC2-505C | |
| Q452EQ25 | Through Beam Sensors |
| PIFM46UHF | Fiber Optics, Plastic Fiber, Opposed, Length 2m |
| PIF26UMFL.200 | Fiber Optics, Glass Fiber, Opposed, Length 1m, Angle |
| PIF26UMFL.315 | |
| EZA-QDR-8 | Screen Accessory |
| K30LXXGPQP-17559 | 1-Color General Purpose Indic, EZ-LIGHT K30L Series |
| T30SP6R | Photoelectric Sensor |
| <u>PIL430U</u> | Fiber Optics, Glass Fiber, Diffuse, Length 1m, Thread |
| M18GRXN | 2-Color Indic |
| M18GRXNQ | M18 Series EZ-LIGHT: 2-Color General Purpose Indic |
| <u>IT2.83SM6</u> | Opposed Mode Individual Glass Fiber |
| LCF04 | |
| PBP46UHF | Fiber Optics |
| PBPF215U | Fiber Optics, Glass Fiber, Opposed, Length 1m, Ferrule |
| PBF26UHF | Fiber Optics, Plastic Fiber, Opposed, Length 1m, Thread |
| SMBPVA16AB | Bracket |
| EZS-1500 | Ezs-1500 1500mm Shield Ez Screen |
| BT210SM8M900 3024858 | |
| <u>T306EQ</u> | Sensor |
| DX70G2X6S4P8 | |
| DX70N2X6S8P4 | |
| <u>QM42VT1</u> | |
| <u>DX80N2Q45VT</u> | |
| 3087097 / DX80G2M6S- PM2 | Gateway |
| K80LGRYB4NQ | |
| MQDC1-530 | |
| P/N: 3031934 Type: Q25SP6LPQ | sensor |
| Q40SP6FF400Q | sensor |
| SMBQ4XFAM10 | |
| Q4XTILAF300-Q8 | photoelectric sensors |
| IVU2RGR12 | |
| <u>RD35</u> | |
| SBF1 BANNER MULTI- BEAM | 3/4 WIRE HIGH SPEED GLASS FIBER |
| PBP BANNER MULTI- BEAM | 3 & 4 WIRE POWER BLOCK |
| LM3 BANNER MULTI- BEAM | LOGIC MODULE |

! 3 Austin Mews, High Street, Hemel Hempstead, HP1 3AF , United Kingdom ! RADWARD LTD United Kingdom

! + 44 20 81571300 ! sales@enapart.co.uk ! www.enapart.co.uk





| Product | Description |
|--|--|
| 26836 / SM312FQD | Sensor |
| NO5-Q08-AP7X2 | BANNER PHOTOELECTRIC SENSOR |
| P/N: 3087097 Type: DX80N2X6S-PM2 | |
| Q45BB6LLP | |
| TL50GYRQ | Light Tower |
| P/N: 3090971 Type: | · · |
| <u>IVU2PRBXC</u> | Barcode Reader |
| P/N: 3088098 Type: WLS28-2XW145DSQ | |
| P/N: 3029512 Type: | |
| RDM35 | |
| <u>P/N: 3082482 Type:</u> <u>LEDGB150X150PW2-XQ</u> | |
| P/N: 3064179 Type: STBVP6 | SAFETY TOUCH BUTTONS |
| BWA-USB1WIRE-001 | DOUBLE-ENDED CORDSETS |
| P/N: 3047558 Type: | |
| Q45ULIU64BCRQ6 | |
| 3032723 / SMB30A | bracket |
| <u>BRT-40X23B</u> | BANNER REFLECTOR |
| <u>BRT-100X18A</u> | Retroreflective Target: Rectangular |
| <u>BRT-80X50CM</u> | BANNER MICROPRISM 80X50MM REFLECTOR USED WITH LT3 |
| <u>BRT-42</u> | BANNER LIGHT REFLECTOR |
| <u>BRT-42A</u> | BANNER RETROREFLECTIVE TARGET: CIRCULAR - DIAMETE |
| BRT-2A | BANNER RETROREFLECTIVE TARGET: CIRCULAR - DIAMETER |
| <u>BRT-51X51BM</u> | BANNER LIGHT REFLECTOR |
| <u>DBQEZLPTL</u> | |
| 3066452 / QS18VP6LPQ8 | Sesor |
| <u>BRT-84</u> | Retroreflective Target: Circular |
| 3040071 / BRT-2X2 | Retroreflective Target: Square |
| <u>VS25EVQ</u> | |
| <u>VS2RP5RQ</u> | |
| P/N: 3070230 Type: | |
| QS30LD | |
| TL50GYRAOSQ | Tower Light |
| K50LGRYPQ | indicator light |
| MBCC-412 | |
| T30SN6RQ | |
| P/N: 3091681 Type: LE250IQ | Optical Sensor |
| Q25AW3LPQ3 | |
| MQAC-406RA | |
| QS18VP6LPQ5 | Sensor |
| QS30DQPMA | |
| | |





| Product | Description |
|---|--|
| P/N: 3033420, Type: | · |
| <u>T186EQ</u> | Optical Photoelectric Sensor |
| P/N: 3033422 Type: T18SP6RQ | |
| <u>SM312W</u> | PHOTOELECTRIC SENSOR |
| Q12AB6FF50Q | |
| R58ECRGB1Q | R58 EXPERT Register Mark Sensor |
| P/N: 3075044 Type: R58ECRGB2Q | R58 EXPERT Register Mark Sensor |
| 3087105 / DX80N2X6S- PM2 | Gateways PM Series Node- LCD for Diagnostics; 2.4 GHz, IP67 /NEMA 6; Inputs:Four selectable NPN/PNP discrete; Two 0-20 mA; Outputs: Four PNP discrete; Two 0-20 mA |
| P/N: 16557, Type: 3GA5- 14 | Optical Edgeguide System |
| P/N: 3061648 Type: QS18VP6CV45 | Photoelectric Sensor |
| SM312LVMHS-50248 | |
| QM42VT2 | Vibration/Temp Sensor |
| MQDEC2-550RA | ELBOW TYPE CABLE SOCKET |
| <u>P/N: 3076420 Type:</u> <u>T8LGRXPQP</u> | |
| P/N: 3033200 Type: SMB18A | |
| QS18VN6LP (61627) | photoelectric sensör |
| SM30PRLBW/30 | |
| <u>SLSR14-300Q8</u> | |
| <u>LM4-2</u> | Photo Sensor Module |
| SBDL1 | Scanner Block |
| <u>PBT</u> | Power Block |
| <u>LM4-2M.1</u> | Logic block |
| P/N: 3078860 Type: DX80N2X6S0P0M4M4 | System interface/media gateway for bus syste |
| P/N: 3800137 Type: DXM100-B1R3 | |
| P/N: 3095667 Type: DX80N2X6S-P6 | Sure Cross® wireless system |
| P/N: 94597 Type: QM42VT1 | |
| P/N: 95664 Type: BWA- BK-001 | |
| D10DPFPQ | Dual Discrete Outputs |
| <u>PIT26U</u> | |
| PKG6Z-2 | |
| P/N: 67380 Type: LT3BDLV | LT3 SERIES 50 M RANGE TIME-OF-FLIGHT LASER SENSOR |
| QT50R-EU-AF2Q | Radar Sensor |
| 3801918 / Q4XTKLAF600- Q8 | Laser Sensor |

! 3 Austin Mews, High Street, Hemel Hempstead, HP1 3AF , United Kingdom ! RADWARD LTD United Kingdom

! + 44 20 81571300 ! sales@enapart.co.uk ! www.enapart.co.uk





| Product | Description |
|------------------------------|--------------------------------------|
| WLB92X1100PBQ | WORK-LIGHT |
| M12FTH4Q | TEMPERATURE AND HUMIDITY SENSOR |
| DXM100-B1R3 | INDUSTRIAL WIRELESS GATEWAY |
| BWA-BK-001 | Mounting apparatus |
| P/N: 94773, Type: | Bracket: For use with WLS27 |
| LMBWLS27SP | Didcket. For use with WES21 |
| P/N: 3036393 Type: | |
| S186ELDQ | DAFFI F CENCOD |
| OASBFV CLL CARMOO | BAFFLE SENSOR |
| SI-LS42WSG | Electromagnet |
| BWA-BK-008 (802370) | Cinala Fadad Caudast |
| QDE-815D | Single Ended Cordset |
| SMBWLS28RA | Hand Mounting World Limbt Chris |
| WLS28-2CW285DXQ | Work Light Strip |
| LTF12IC2LDQ | Opto-sensor |
| P/N: 3029409, Type: S186E | Optical Photoelectric Sensor |
| P/N: 3029408, Type: | |
| <u>S18SN6R</u> | Optical Photoelectric Sensor |
| P/N: 3033421, Type: | Optical Photoelectric Sensor |
| T18SN6RQ | Optical Photoelectric Serisol |
| Q12AB6FF30Q | CMI cap tightening sensor |
| <u>87489</u> | Industrial LED Light Bar |
| <u>87490</u> | Industrial LED Light Bar |
| <u>Q453E</u> | |
| Q45VR3R | |
| <u>80458</u> | Ultrasonic material detection sensor |
| <u>T30SN6FF200</u> | sensor |
| SSA-EB1PLYR-12ECQ8 | |
| OTBVR81QD | |
| OTBVP6QD | |
| <u>OTBA5QD</u> | |
| MQDEC2-415 | |
| K50APLPGXDQ | |
| <u>AG4-4E</u> | |
| <u>85068</u> | |
| 805002 | |
| <u>72154</u> | |
| 18348 / AHC2158496 | BANNER LMB30RA |
| <u>807139</u> | |
| <u>807138</u> | |
| <u>02879</u> | |
| K50LGRAL1YPQ | Panel Mount Indicator |
| 32311 / PVL500PQ | |
| | |





| Product | Description |
|------------------------|---|
| Q3XTBLD-Q8 | Laser Contrast Sensor |
| 25620 | MINI-BEAM FIBER OPTIC AMPLIFIER |
| 10137 / SA-M30TE12 | |
| 10443 / SOP-E12-150A | |
| 37628 / Q45AD9DLQ | Rugged rectangle sensor |
| 32470 / T18SP6FF50 | rtuggou reetangte eeneet |
| 26892 / SM312WQD | Photoelectric Sensor |
| WLS28XW285XQ | Work light strip |
| 3029988 / SSA-EB1PLXR- | |
| 12ED1Q8 | Surface Based Illuminated Emergency Stop Button |
| 3085064 / XS26-2DE | Safety Controller |
| 29510 / S18SP6RQ | <u> </u> |
| 801976 / PGIRS66U-100 | FIBER OPTIC SENSOR |
| 87576 / DF-G3-PS-2M | FIBER OPTIC AMPLIFIER |
| 20065 / IAT23PMSS | |
| SX5-B | |
| MIAD9LVAGQ | Opto sensor |
| QS18VP6LLPQ5 | Photoelectric Sensor |
| PBA | Power Block |
| SC10-2ROE | Safety Controller |
| Q12RB6RQ5 | Sensor |
| Q126EQ5 | Sensor |
| 3077763 / Q20NLP | Photoelectric sensor |
| SMBQ20L | Bracket |
| SLLP23-420P88 | 2.48 |
| QS18UPAQ8 | sensor |
| MQDC-415 | Cable Assembly |
| 61631 \ QS18VP6LPQ | Gage |
| 89583 \ SLLP40-910P55 | J. W. S. W. |
| OTBVR81 | |
| T18SP6FF100Q | |
| B-TL70-Q8 | |
| MQDC1-506 | |
| 3087105 / DX80G2M6S- | |
| <u>PM2</u> | WIRELES SIGNAL SENDER |
| BT210SM900 | Fiber optik cable(red eye) |
| K50LGRXP | Panel Mount Indicator |
| K30LGRYP | Panel Mount Indicator |
| SLSP14-1500P88 | |
| SLSP14-450P88 | |
| K30LGRXPQ | |
| VS25EQ | ULTRA THIN MINIATURE SENSOR |
| 3025366 / QT50R-EU-AFH | |
| 3061636 / QS18VP6LV | |
| | |





| Product | Description |
|--|---------------------------------|
| p/n: 3097843, Type: | Work light bar |
| WLB32ZC1130EPBQM | - |
| P/N: 71817, Type: LX24RQ | LX Series |
| P/N: 71802, Type: LX24EQ | |
| SME312LPCQD | |
| 3072132 / Q12RB6LPQ | photocell |
| Q12RP6RQ3 | MINIATURE SELF-CONTAINED SENSOR |
| BRT-44X29A6 | Reflector |
| <u>OPBT2QDH</u> | Sensor |
| OSBF | Sensor Head |
| 3071817 / LX24RQ | RECEIVER PHOTOCELL |
| 3071802 / LX24EQ | EMITTER PHOTOCELL |
| 45LM58 | Mechanical switch |
| Q45BB6FQ5 (38667) | RUGGED FIBER OPTIC AMPLIFIER |
| Q45BB6LVAGCQ5-63649 | |
| IAT23S | |
| IAT26S | |
| ES-UA-5A | CAFETY OWITCH ORDING LOOK |
| SI-LS42DMSIF | SAFETY SWITCH SPRING LOCK |
| SM912FQD | |
| S18AW3D | |
| SSA-EB1P-02 | |
| <u>SMBQ4XFAM12</u> <u>MAR4816PX485Q</u> | |
| MAE4816Q | |
| RP-LS42F-75L | |
| WLH60XW640B | |
| T30R-1515-KIQ | |
| BWA-BK-013 | Bracket |
| AT-FM-10K | Didonet |
| P/N: 71561, Type: | |
| <u>QS30EXQ</u> | sensor |
| MQDEC3-530SS | |
| MQDC-4506SS | |
| RSD1QP | |
| MQDC2S-815 \ 3070976 | connecting cable |
| <u>3076959 /</u> | LED display, beacon |
| K50LGRYBWPQ8 | |
| SI-MAGB2SM | COVER MAGNETIC SENSOR RECEIVER |
| 79217 / SLM20B6 | rugged metal slot sensor |
| SM312FQD-40396 | Sensor |
| 3002661 / LX3EQ | Optical Sensor |
| QS30FF400 | |
| <u>SM312D</u> | Photoelectric Sensor |





| Product | Description |
|--------------------------|---|
| MQDC-406 | Cable Assembly |
| LS2TR30-600Q8 | Light Curtain Receiver |
| LT3PUQ-79783 | Sensor |
| SM912LVAG | |
| Q60VR3AFV1000 | |
| QDEG-8100D | |
| Q45BW13LP | rectangle sensor |
| SM2A31RQD | Mini-beam series industry standard sensor |
| OTBVN6 | |
| P/N: 58979, Type: BRT-84 | retroreflective target reflector |
| MQDEC2-515 | Cable Assembly |
| ES-FA-9AA | |
| T30SN6R W/30 EZ-BEAM | Sensor receiver |
| T306E W/30 EZ-BEAM | Sensor |
| K50L2RGBKQ | programmable multicolor indicator |
| K30APT2FXBF2QP | Indicator |
| S18-2VPDL-Q8 | Photoelectric Sensor |
| S18RW3DL | Photoelectric Sensor |
| <u>88407</u> | |
| SM312FQD | Optic amplifier |
| MPC3 | Amplifier Module |
| VSM-2M5APD100-2M | |
| 27060 / SE61RNCMHS | |
| 25971 / SE61EMHS | |
| TL70BGYRAPQ | Stack Light Complete Unit |
| <u>SOK-TL70-150A</u> | Pipe Brkt Kit |
| MAQDC-830 | Cable Assembly |
| MAQDC-8125 | Single-Ended Cordset |
| STBVR81 / 64190 | Self-Checking Touch Button |
| QS18EP6XLPCQ5 | Polarized Optical Sensor |
| WLC60XW640AQ | Work Light |
| <u>EA5E600Q</u> | Optical Sensor |
| EA5R600PUXMODSRLCQ | measuring light curtain |
| <u>45LM5</u> | |
| 3092336 / TL70GYRQ | LED display |
| P/N: 8004811 Type: | connector |
| WAKC4K | |
| FIC-M12F4 | |
| S18SP6DLQ | Photoelectric Sensor |
| 3002667 / LX3RQ | Photoelectric Sensor |
| 3077761 / Q20PLP | sensor |
| QS18UPA | Optical Sensor |
| 810628 / S15C-I-MQ | In-Line Converter |
| 812240 / DXMR90-X1 | Controller |





| Product | Description |
|--|--|
| 812041 / R45C-B22-SQ | In-Line Converter |
| <u>3096764 /</u> | Assembly sensor |
| K50APT2GRYF2Q | Assembly sensor |
| MQDC2S-815 | Single-ended cordset |
| 3097183 / VELC85-BG | image processing, lens cover |
| 3097184 / VELC85-PC | image processing, lens cover |
| <u>3047553 /</u> <u>Q45ULIU64ACRQ</u> | ultrasonic sensor, reflection sensor |
| PTL110S-FF100TD3- QP150 / 805482 | LED light modules |
| <u>SLPR25-550P8</u> | receiver |
| DELPE-81D | |
| LPA-MBK-11 | |
| QS18VP6LDQ8 | Diffuse Optical Sensor |
| 3087484 / WLB32C1130PBQ | Work lamps, line lamp |
| TUR3802557 | |
| T18SP6LPQ | photoelectric sensor |
| S30SP6RQ | Photoelectric sensor, thru-beam sensor (receiver) |
| <u>S306EQ</u> | Photoelectric sensor, thru-beam sensor (transmitter) |
| 51127 / AHC1929749 | BANNER MQDC1-506 |
| 83214 / AHC1965454 | BANNER TL50GYRAQ |
| R55FVQ-14341 | |
| SLSE14-600Q8 | Personal protection light curtain, transmitter |
| SMB30SC | Mounting Fixings Bracket |
| OTBVP6 | |
| <u>T18-2VPRL-Q8</u> | Through-Beam Optical Sensor |
| 3029508 / S18SP6DQ | Photoelectric sensor, reflection light sensor |
| 3053981 / Q45VR3LV | Photoelectric sensor, reflection light barrier |
| MBCC2-506 | Cordset |
| SM91RFQD | SIGNAL TURNER |
| <u>36150</u> | CYLINDRICAL INDUCTIVE SENSOR PNP |
| <u>25530</u> | SIGNAL CONVERTER |
| WLS27PXRGBW285DSQ | LIGHT STRIP |
| MQDC-506 | PRO CONVERTER |
| CSB-M1251FM1251M | CONNECTOR |
| PSW-24-1 | DC POWER SUPPLY |
| <u>ESL-41/60-ENES</u> | Energeney stop |
| MQDEC2-430RA | Cordset |
| T18-2VPFF100IR-Q8 | Background Suppression Optical Sensor |
| BA1.53SMETAM600 | Photoelectric Sensor |
| WLH60XW340GB | |
| Q4XTBLAF500-Q8 | Laser distance sensor |
| <u>SLM10B6, 74965</u> | |

! 3 Austin Mews, High Street, Hemel Hempstead, HP1 3AF , United Kingdom ! RADWARD LTD United Kingdom

! + 44 20 81571300 ! sales@enapart.co.uk ! www.enapart.co.uk





| Product | Description |
|------------------------|--|
| T18-2VPRL-Q8, 802607 | |
| QS30EXQ | photoelectric sensor |
| QS30RRXQ | photoelectric sensor |
| LX3EQ | Safety Light Curtain |
| M18TUP14Q-77118 | Temperature sensor |
| VE200G1A | image processing, smart camera |
| VE201G1A | image processing, smart camera |
| SI-LS83PBD | image processing, emart earners |
| 3813083 / | |
| K100PLRGB7AQ | tower light |
| K50LGRYP | Rearable |
| S18UBAQ | proximity sensor |
| MACP-1 | Safety Light Curtain |
| BMEL3032A | Photoelectric Sensor |
| BMRL3032A | Photoelectric Sensor |
| WLB32ZC850EPBQMEF | Work light bar |
| R45C-KUU-UUQ | Interface Module |
| WLS27PXRGBW570DSQ | Led Lighting Bars & Strips |
| S15CM-PF-UQ | Circular Metric Connector |
| BFW-M12M4-6X | Circular Metric Connector |
| BFW-M12F4-6X | Circular Metric Connector |
| 87852 / LMBWLB32-180S | Mounting Bracket |
| 73661 / MQDEC2-406 | Cordset |
| S18-2VPLPC-Q8 | Photoelectric Sensor, Polarized Retro, 6m, 10-30VDC, PNP, QD, S18-2 |
| BRT-60X40C | Reflector, Rectangular, 60mm x 40mm |
| Q60BB6AF2000Q | Photoelectric Sensor, Adjustable Field IR, 2m, 10-30VDC, NPN/PNP, QD |
| T30UXDCQ8 | |
| Q240RA-Z2CN | Radar Sensor |
| QS18VN6RBQ5 | Opto-sensor, one-way light barrier (receiver) |
| SLPMP25-690P128 | safety light curtains |
| QS18VP6LQ | photoelectric sensors |
| <u>SMU315D</u> | Photoelectric Sensor |
| OTBA5 | photoelectric sensor |
| SM312F | Photoelectric Sensor |
| 3022317 / IAT2.53SM600 | |
| QT50R-EU-AFHQ | R-Gage Series Photoelectric Sensors |
| QCM50-K1D60-Q8-4 | BRACKET |
| SMBQCM50L | Stainless Steel Right-Angle |
| CSB-M1251M1251B | DIVERTER CABLE |
| T30SP6FF400 | cylindrical optical sensor |
| QS18EN6D | Photoelectric Sensor |
| QS30EDVQ | Diffuse Optical Sensor |
| Q12AP6FF30Q3 | Background Suppression Optical Sensor |
| GIZAI OI I OOQO | 9 |





| Product | Description |
|---------------------------|---|
| 86746 / LE550IQ | Distance Sensor |
| 45LM5D | |
| WLC90IGL30RQ | LED LAMP |
| QS30EXQ-17527 | Photoelectric Sensor |
| QS30ARXQ-17528 | Photoelectric Sensor |
| QS30ARXQ-17530 | Photoelectric Sensor |
| QS30EXQ-17529 | Photoelectric Sensor |
| OTBVP6QDH | Photoelectric Sensors |
| RP-LM40D-6 | cable pull switch |
| 802619 / T18-2NAES-Q8 | Photoelectric Sensor |
| 810672 / WL50-3W | work lamps, spot light |
| RSBF | |
| RLM8 | |
| TM18VP6LPQ8 | Retroreflective Optical Sensor |
| <u>T18-2NAEL-Q8</u> | Through-Beam Optical Sensor |
| 45007 / BRT-41AHT | RETROREFLECTIVE TARGET |
| SM30SRLMC1 W/30 70987 | Through-Beam Optical Sensor 492.13' (150m) NPN/PNP - Dark-ON/Light-ON |
| SMA30SELMC1 W/30 70923 | Through-Beam Optical Sensor 492.13' (150m) |
| <u>IA23S</u> | Fibre Optic Sensor |
| Q10AP6DQ | Photoelectric Sensor |
| 802139 / K30L2RGB7 | |
| 803770 / MQDC-506-USB | usb |
| 77986 / K50LGRYA120Q | Indicator Light |